



Ci specifications sheet

OBSESSED WITH HIGH RESOLUTION

Tall Rectangle



| Model | Ci5160RL-THX | | Ci3160RL-THX | | Ci3160RLb-THX | |
|---|---|--------------------------|--|--------------------------|---|--------------------|
| Series | R Series | | R Series | | R Series | |
| Nominal impedance | 4Ω | | 4Ω | | 4Ω | |
| Sensitivity (2.83V/1m) | 90dB | | 90dB | | 92dB | |
| Frequency response (±6dB) open-backed | 40Hz - 28kHz | | 45Hz - 28kHz | | 20Hz - 140Hz | |
| Crossover frequency | 300Hz, 2.4kHz | | 340Hz, 2.5kHz | | - | |
| Drive units | LF | 4 x 160mm (6.5in.) Uni-Q | LF | 2 x 160mm (6.5in.) Uni-Q | LF | 3 x 160mm (6.5in.) |
| | MF | 160mm (6.5in.) | MF | 160mm (6.5in.) | MF | - |
| | HF | 25mm (1in.) | HF | 25mm (1in.) | HF | - |
| Required amplifier | - | | - | | KEF KASA500 | |
| Recommended amplifier power | 40 - 250 W | | 30 - 180 W | | - | |
| Product external dimensions (H x W x D) | 1070 x 230 x 105.7 mm (42.13 x 9.06 x 4.16 in.) | | 680 x 230 x 105.7 mm (26.77 x 9.06 x 4.16 in.) | | 680 x 230 x 96 mm (26.77 x 9.06 x 3.78 in.) | |
| Cut-out dimensions (H x W) | 1052 x 209 mm (41.42 x 8.23 in.) | | 660 x 209 mm (25.98 x 8.23 in.) | | 660 x 209 mm (25.98 x 8.23 in.) | |
| Net weight | 19kg (41.89 lbs) | | 11.7kg (25.79 lbs) | | 10.9kg (24.1 lbs) | |
| Mounting depth from surface | 99mm (3.9in.) | | 99mm (3.9in.) | | 88.5mm (3.84in.) | |
| Optional rough in frame | RIF5160L | | RIF3160L | | RIF3160L | |



| Model | Ci4100QL-THX | | Ci4100QLb | |
|---|---|------------------------|---|------------------|
| Series | Q Series | | Q Series | |
| Nominal impedance | 4Ω | | 4Ω | |
| Sensitivity (2.83V/1m) | 89dB | | 90dB | |
| Frequency response (±6dB) open-backed | 55Hz - 28kHz | | 35Hz - 120Hz | |
| Crossover frequency | 2.2kHz | | - | |
| Drive units | LF | 3 x 100mm (4in.) Uni-Q | LF | 4 x 100mm (4in.) |
| | MF | 100mm (4in.) | MF | - |
| | HF | 19mm (0.75in.) | HF | - |
| Required amplifier | - | | KEF KASA500 | |
| Recommended amplifier power | 10 - 150 W | | - | |
| Product external dimensions (H x W x D) | 490 x 128 x 81 mm (19.29 x 5.04 x 3.19 in.) | | 490 x 128 x 81 mm (19.29 x 5.04 x 3.19 in.) | |
| Cut-out dimensions (H x W) | 476 x 114 mm (18.74 x 4.49 in.) | | 476 x 114 mm (18.74 x 4.49 in.) | |
| Net weight | 3kg (6.61 lbs) | | 3kg (6.61 lbs) | |
| Mounting depth from surface | 76mm (3in.) | | 76mm (3in.) | |
| Optional rough in frame | RIF4100L | | RIF4100L | |



OBSESSED WITH HIGH RESOLUTION

Ci specifications sheet

Rectangle



| Model | Ci200QL | Ci160QL | Ci160.2CL |
|---|--|--|--|
| Series | Q Series | Q Series | C Series |
| Nominal impedance | 8Ω | 8Ω | 8Ω |
| Sensitivity (2.83V/1m) | 90dB | 89dB | 89dB |
| Frequency response (±6dB) open-backed | 35Hz - 34kHz | 38Hz - 34kHz | 52Hz - 20kHz |
| Crossover frequency | 2.5kHz | 3.0kHz | 2.5kHz |
| Drive units | LF 200mm (8in.) Uni-Q HF 25mm (1in.) | 160mm (6.5in.) Uni-Q 19mm (0.75in.) | 160mm (6.5in.) Uni-Q 16mm (0.6in.) |
| Recommended amplifier power | 10 - 150 W | 10 - 125 W | 10 - 100 W |
| Product external dimensions (H x W x D) | 369 x 273 x 106 mm (14.53 x 10.75 x 4.17 in.) | 303 x 223 x 97.5 mm (11.93 x 8.78 x 3.84 in.) | 303 x 223 x 88.7 mm (11.93 x 8.78 x 3.49 in.) |
| Cut-out dimensions (H x W) | 334 x 238 mm (13.15 x 9.37 in.) | 274 x 194 mm (10.79 x 7.64 in.) | 274 x 194 mm (10.79 x 7.64 in.) |
| Net weight | 2.6kg (5.77 lbs) | 2.05kg (4.51 lbs) | 1.6kg (3.5 lbs) |
| Mounting depth from surface | 99.8mm (3.93in.) | 91mm (3.58in.) | 84.5mm (3.33in.) |
| Optional rough in frame | RIF200L | RIF160L | RIF160L |
| Optional rear enclosure | RNC200L | RNC160L | RNC160L |

Square



| Model | Ci200RS-THX | Ci200Qsb-THX Passive Mode (Crossover "ON") | Ci200Qsb-THX Active Mode (KASA500) |
|---|--|---|---|
| Series | R Series | Q Series | Q Series |
| Nominal impedance | 4Ω | 6Ω | N/A |
| Sensitivity (2.83V/1m) | 90dB | 85dB | N/A |
| Frequency response (±6dB) open-backed | 33Hz - 28kHz | 40Hz - 100Hz | 18Hz - 140Hz |
| Crossover frequency | 2.2kHz | 100Hz | N/A |
| Drive units | LF 200mm (8in.) Uni-Q HF 38mm (1.5in.) | 200mm (8in.) - | 200mm (8in.) - |
| Required amplifier | - | - | KEF KASA500 |
| Recommended amplifier power | 10 - 190 W | 10 - 150 W | - |
| Product external dimensions (H x W x D) | 273 x 273 x 132.6 mm (10.75 x 10.75 x 5.22 in.) | 273 x 273 x 106 mm (10.75 x 10.75 x 4.17 in.) | 273 x 273 x 106 mm (10.75 x 10.75 x 4.17 in.) |
| Cut-out dimensions (H x W) | 240 x 240 mm (9.45 x 9.45 in.) | 238 x 238 mm (9.37 x 9.37 in.) | 238 x 238 mm (9.37 x 9.37 in.) |
| Net weight | 3.6kg (7.94 lbs) | 3.3kg (7.28 lbs) | 3.3kg (7.28 lbs) |
| Mounting depth from surface | 127mm (5in.) | 101.6mm (4in.) | 101.6mm (4in.) |
| Optional rough in frame | RIF200S | RIF200S | RIF200S |
| Optional rear enclosure | N/A | N/A | N/A |

Not all models / finishes are available in all markets. Contact your local dealer for specific range details.
KEF reserves the right, in line with continuing research and development, to amend or change specifications. E&OE.
THX and the THX logo are trademarks of THX Ltd. which are registered in some jurisdictions. All rights reserved.

KEF.COM



Ci specifications sheet

OBSESSED WITH HIGH RESOLUTION

Square



| Model | Ci200QS | Ci160QS | Ci130QS | Ci100QS |
|---|--|---|---|---|
| Series | Q Series | Q Series | Q Series | Q Series / Soundlight |
| Nominal impedance | 8Ω | 8Ω | 8Ω | 4Ω |
| Sensitivity (2.83V/1m) | 90dB | 89dB | 87dB | 88dB |
| Frequency response (±6dB) open-backed | 35Hz - 34kHz | 38Hz - 34kHz | 45Hz - 34kHz | 80Hz - 27kHz |
| Crossover frequency | 2.5kHz | 3.0kHz | 3.8kHz | 3kHz |
| Drive units | LF 200mm (8in.) Uni-Q | LF 160mm (6.5in.) Uni-Q | LF 130mm (5.25in.) Uni-Q | LF 100mm (4in.) Uni-Q |
| | HF 25mm (1in.) | HF 19mm (0.75in.) | HF 19mm (0.75in.) | HF 19mm (0.75in.) |
| Recommended amplifier power | 10 - 150 W | 10 - 125 W | 10 - 100 W | 10 - 50 W |
| Product external dimensions (H x W x D) | 273 x 273 x 106 mm (10.75 x 10.75 x 4.17 in.) | 223 x 223 x 97 mm (8.78 x 8.78 x 3.82 in.) | 184 x 184 x 84 mm (7.24 x 7.24 x 3.31 in.) | 127 x 127 x 76 mm (5.0 x 5.0 x 2.99 in.) |
| Cut-out dimensions (H x W) | 238 x 238 mm (9.37 x 9.37 in.) | 194 x 194 mm (7.64 x 7.64 in.) | 158 x 158 mm (6.22 x 6.22 in.) | 112 x 112 mm (4.41 x 4.41 in.) |
| Net weight | 2.4kg (5.3 lbs) | 1.88kg (4.14 lbs) | 1.4kg (3.1 lbs) | 0.67kg (1.48 lbs) |
| Mounting depth from surface | 99.8mm (3.93in.) | 91mm (3.58in.) | 77.9mm (3.07in.) | 72mm (2.83in.) |
| Optional rough in frame | RIF200S | RIF160S | RIF130S | RIF100S |
| Optional rear enclosure | RNC200S | RNC160S | RNC130S | RNC100S |



| Model | Ci160.2CS | Ci130.2CS | Ci160CSds | Ci160TS |
|---|---|---|---|---|
| Series | C Series | C Series | C Series | T Series |
| Nominal impedance | 8Ω | 8Ω | 8Ω | 8Ω |
| Sensitivity (2.83V/1m) | 89dB | 87dB | 91dB | 87dB |
| Frequency response (±6dB) open-backed | 52Hz - 20kHz | 52Hz - 20kHz | 50Hz - 20kHz | 110Hz - 24kHz |
| Crossover frequency | 2.5kHz | 2.5kHz | 3.2kHz | 1.7Hz |
| Drive units | LF 160mm (6.5in.) Uni-Q | LF 130mm (5.25in.) Uni-Q | LF 160mm (6.5in.) | LF 115mm (4.5in.) Dual layer |
| | HF 16mm (0.6in.) | HF 16mm (0.6in.) | HF 2 x 19mm (0.75in.) | HF 25mm (1in.) |
| Recommended amplifier power | 10 - 100 W | 10 - 80 W | 10 - 80 W | 10 - 100 W |
| Product external dimensions (H x W x D) | 223 x 223 x 88.7 mm (8.78 x 8.78 x 3.49 in.) | 184 x 184 x 81 mm (7.24 x 7.24 x 3.19 in.) | 223 x 223 x 90.5 mm (8.78 x 8.78 x 3.56 in.) | 222.8 x 222.8 x 41 mm (8.77 x 8.77 x 1.61 in.) |
| Cut-out dimensions (H x W) | 194 x 194 mm (7.64 x 7.64 in.) | 158 x 158 mm (6.22 x 6.22 in.) | 194 x 194 mm (7.64 x 7.64 in.) | 194 x 194 mm (7.64 x 7.64 in.) |
| Net weight | 1.5kg (3.3 lbs) | 1.2kg (2.7 lbs) | 1.80kg (4.0 lbs) | 1.05kg (2.31 lbs) |
| Mounting depth from surface | 84.5mm (3.33in.) | 77.1mm (3.03in.) | 84.5mm (3.33in.) | <36mm (1.42in.) |
| Optional rough in frame | RIF160S | RIF130S | RIF160S | RIF160S |
| Optional rear enclosure | RNC160S | RNC130S | RNC160S | RNC160S |



Ci specifications sheet

OBSESSED WITH HIGH RESOLUTION

Round



| Model | | Ci200RR-THX | Ci200TRb Passive Mode | Ci200TRb Active Mode (KASA500) |
|---|------------|--------------------|----------------------------------|---|
| Series | | R Series | T Series | T Series |
| Nominal impedance | | 4Ω | - | - |
| Nominal impedance stereo mode | | - | 2 × 8Ω | 2 × 8Ω |
| Nominal impedance mono mode | | - | 16Ω | 16Ω |
| Sensitivity (2.83V/1m) | | 90dB | 87dB | 87dB |
| Frequency response (±6dB) open-backed | | 33Hz - 28kHz | 42Hz - 120Hz | 32Hz - 120Hz |
| Crossover frequency | | 2.2kHz | N/A | N/A |
| Drive units | LF | 200mm (8in.) Uni-Q | 200mm (8in.) | 200mm (8in.) |
| | HF | 38mm (1.5in.) | - | - |
| Required amplifier | | - | - | KEF KASA500 |
| Recommended amplifier power | | 10 - 190 W | 10 - 125 W | - |
| Product external dimensions | Diameter Ø | 290mm (11.42in.) | 290mm (11.42in.) | 290mm (11.42in.) |
| | Depth | 132.6mm (5.22in.) | 63mm (2.48in.) | 63mm (2.48in.) |
| Cut-out dimensions | Diameter Ø | 238mm (9.37in.) | 240mm (9.45in.) | 240mm (9.45in.) |
| Net weight | | 3.6kg (7.94 lbs) | 1.7kg (3.75 lbs) | 1.7kg (3.75 lbs) |
| Mounting depth from surface with back can | | 126.5mm (4.98in.) | 59mm (2.32in.) | 59mm (2.32in.) |
| Optional rough in frame | | RIF200R | RIF200R | RIF200R |
| Optional rear enclosure | | - | RNC200R | RNC200R |



| Model | | Ci200QR | Ci160QR | Ci130QR |
|---|------------|----------------------|----------------------|-----------------------|
| Series | | Q Series | Q Series | Q Series |
| Nominal impedance | | 8Ω | 8Ω | 8Ω |
| Sensitivity (2.83V/1m) | | 90dB | 89dB | 87dB |
| Frequency response (±6dB) open-backed | | 35Hz - 34kHz | 38Hz - 34kHz | 45Hz - 34kHz |
| Crossover frequency | | 2.2kHz | 3.0kHz | 3.8kHz |
| Drive units | LF | 200mm (8.0in.) Uni-Q | 160mm (6.5in.) Uni-Q | 130mm (5.25in.) Uni-Q |
| | HF | 25mm (1in.) | 19mm (0.75in.) | 19mm (0.75in.) |
| Recommended amplifier power | | 10 - 150 W | 10 - 125 W | 10 - 100 W |
| Product external dimensions | Diameter Ø | 289.6mm (11.4in.) | 234.6mm (9.24in.) | 193.4mm (7.61in.) |
| | Depth | 109.8mm (4.32in.) | 98mm (3.86in.) | 83.3mm (3.28in.) |
| Cut-out dimensions | Diameter Ø | 240mm (9.45in.) | 196mm (7.71in.) | 158mm (6.22in.) |
| Net weight | | 2.4kg (5.28 lbs) | 1.8kg (3.96 lbs) | 1.35kg (2.97 lbs) |
| Mounting depth from surface with back can | | 103.3mm (4.07in.) | 91mm (3.58in.) | 77.8mm (3.06in.) |
| Optional rough in frame | | RIF200R | RIF160R | RIF130R |
| Optional rear enclosure | | RNC200R | RNC160R | RNC130R |



Ci specifications sheet

OBSESSED WITH HIGH RESOLUTION

Round



| Model | | Ci200.2CR | Ci160.2CR | Ci130.2CR | Ci160CRds |
|---|------------|----------------------|----------------------|-----------------------|---------------------------------|
| Series | | C Series | C Series | C Series | C Series |
| Nominal impedance | | 8Ω | 8Ω | 8Ω | 8Ω |
| Sensitivity (2.83V/1m) | | 90dB | 89dB | 87dB | 91dB |
| Frequency response (±6dB) open-backed | | 45Hz - 20kHz | 52Hz - 20kHz | 52Hz - 20kHz | 50Hz - 20kHz |
| Crossover frequency | | 3.0kHz | 2.5kHz | 2.5kHz | 3.2kHz |
| Drive units | LF | 200mm (8.0in.) Uni-Q | 160mm (6.5in.) Uni-Q | 130mm (5.25in.) Uni-Q | Dual voice coil: 160mm (6.5in.) |
| | HF | 16mm (0.6in.) | 16mm (0.6in.) | 16mm (0.6in.) | 2 x 19mm (0.75in.) |
| Recommended amplifier power | | 10 - 125 W | 10 - 100 W | 10 - 80 W | 10 - 80 W |
| Product external dimensions | Diameter Ø | 289.6mm (11.4in.) | 234.6mm (9.24in.) | 193.4mm (7.61in.) | 234.6mm (9.24in.) |
| | Depth | 103.3mm (4.07in.) | 88.7mm (3.49in.) | 82.3mm (3.24in.) | 93mm (3.66in.) |
| Cut-out dimensions | Diameter Ø | 240mm (9.45in.) | 196mm (7.71in.) | 158mm (6.22in.) | 196mm (7.71in.) |
| Net weight | | 1.7kg (3.7 lbs) | 1.4kg (3.1 lbs) | 1.3kg (2.8 lbs) | 1.80kg (4.0 lbs) |
| Mounting depth from surface with back can | | 97.2mm (3.83in.) | 84.5mm (3.33in.) | 77.7mm (3.06in.) | 86mm (3.36in.) |
| Optional rough in frame | | RIF200R | RIF160R | RIF130R | RIF160R |
| Optional rear enclosure | | RNC200R | RNC160R | RNC130R | RNC160R |



| Model | | Ci200ER | Ci160ER | Ci130ER | Ci160TR |
|---|------------|-------------------|-------------------|-------------------|---------------------------|
| Series | | E Series | E Series | E Series | T Series |
| Nominal impedance | | 8Ω | 8Ω | 8Ω | 8Ω |
| Sensitivity (2.83V/1m) | | 90dB | 89dB | 87dB | 87dB |
| Frequency response (±6dB) open-backed | | 45Hz - 20kHz | 52Hz - 20kHz | 52Hz - 20kHz | 110Hz - 24kHz |
| Crossover frequency | | 2.8kHz | 2.8kHz | 2.8kHz | 1.7kHz |
| Drive units | LF | 200mm (8in.) | 160mm (6.5in.) | 130mm (5.25in.) | 115mm (4.5in.) dual layer |
| | HF | 16mm (0.6in.) | 16mm (0.6in.) | 16mm (0.6in.) | 25mm (1in.) |
| Recommended amplifier power | | 10 - 125 W | 10 - 100 W | 10 - 80 W | 10 - 100 W |
| Product external dimensions | Diameter Ø | 289.6mm (11.4in.) | 234.6mm (9.24in.) | 193.4mm (7.61in.) | 234.6mm (9.24in.) |
| | Depth | 103.3mm (4.07in.) | 88.7mm (3.49in.) | 81mm (3.19in.) | 40mm (1.57in.) |
| Cut-out dimensions | Diameter Ø | 240mm (9.45in.) | 196mm (7.71in.) | 158mm (6.22in.) | 196mm (7.71in.) |
| Net weight | | 1.6kg (3.6 lbs) | 1.4kg (3.1 lbs) | 1.2kg (2.7 lbs) | 1kg (2.2 lbs) |
| Mounting depth from surface with back can | | 97.2mm (3.83in.) | 85.2mm (3.35in.) | 77.5mm (3.05in.) | <36mm (1.42in.) |
| Optional rough in frame | | RIF200R | RIF160R | RIF130R | RIF160R |
| Optional rear enclosure | | RNC200R | RNC160R | RNC130R | RNC160R |



OBSESSED WITH HIGH RESOLUTION

Ci specifications sheet

Soundlight



| Model | | Ci100.2QR | Ci50R |
|--|------------------|-----------------------|-----------------------|
| Series | | Soundlight / Q Series | Soundlight / C Series |
| Nominal impedance | | 4Ω | 6Ω |
| Sensitivity (2.83V/1m) | | 83dB | 82dB |
| Frequency response (±6dB) open-backed | | 90Hz - 27kHz | 125Hz - 20kHz |
| Frequency response (±6dB) with back can / rear enclosure | | 130Hz - 27kHz | 170Hz - 20kHz |
| Crossover frequency | | 3.5kHz | - |
| Drive units | LF | 75mm (3in.) Uni-Q | - |
| | MF | - | 50mm (2.0in.) |
| | HF | 16mm (0.6in.) | - |
| Recommended amplifier power | | 10 - 50 W | 10 - 30 W |
| Product external dimensions | Diameter Ø | 136mm (5.4in.) | 80mm (3.15in.) |
| | Depth | 57mm (2.2in.) | 52mm (2.05in.) |
| Cut-out dimensions | Diameter Ø | 118mm (4.6in.) | 65mm (2.56in.) |
| Net weight | | 0.50kg (1.10 lbs) | 0.135kg (0.31 lbs) |
| Mounting depth from surface | With back can | 103mm (4.1in.) | 90mm (3.54in.) |
| | Without back can | 52mm (2in.) | 50mm (1.97in.) |
| Optional rough in frame | | RIF100R | - |
| Optional rear enclosure | | RNC100R | CI50CAN |

Commercial Round



| Model | | Ci160QCT** | Ci115QCT** | Ci110FCT** | Ci160ST** |
|--|------------|---|---|---|---|
| Series | | Q Series | Q Series | Classic Series | Classic Series |
| Nominal impedance | | 8Ω | 8Ω | 8Ω | 4Ω |
| Sensitivity (2.83V/1m) | | 89dB | 86dB | 89dB | 85dB |
| Frequency response (±6dB) with back can / rear enclosure | | 60Hz - 20kHz | 70Hz - 20kHz | 110Hz - 18kHz | 60Hz - 130Hz |
| Crossover frequency | | 2.8kHz | 2.3kHz | - | - |
| Drive units | LF | 160mm (6.5in.) Uni-Q | 115mm (4.5in.) Uni-Q | 110mm (4.3in.) | 160mm (6.5in.) |
| | HF | 19mm (0.75in.) | 19mm (0.75in.) | - | - |
| Recommended amplifier power | | 10 - 100 W | 15 - 80 W | 10 - 100 W | 20 - 100 W |
| Transformer taps | | 70V: 7.5W, 15W, 30W, 60W 100V: 15W, 30W, 60W | 70V: 4W, 8W, 15W, 30W 100V: 8W, 15W, 30W | 70V: 4W, 8W, 15W, 30W 100V: 8W, 15W, 30W | 70V: 7.5W, 15W, 30W, 60W 100V: 15W, 30W, 60W |
| Product external dimensions | Diameter Ø | 275mm (10.83in.) | 220mm (8.66in.) | 220mm (8.66in.) | 275mm (10.83in.) |
| | Depth | 188mm (7.40in.) | 160mm (6.30in.) | 110mm (4.33in.) | 188mm (7.40in.) |
| Cut-out dimensions | Diameter Ø | 240mm (9.45in.) | 196mm (7.71in.) | 196mm (7.71in.) | 240mm (9.45in.) |
| Net weight | | 4.27kg (9.4 lbs) | 2.7kg (5.94 lbs) | 2.25kg (4.95 lbs) | 3.4kg (7.48 lbs) |
| Mounting depth from surface with back can | | 185mm (7.28in.) | 157mm (6.18in.) | 107mm (4.21in.) | 185mm (7.28in.) |
| Optional rough in frame | | RIF200R | RIF160R | RIF160R | RIF200R |

** UL2043 and UL1480-5 approved

Not all models / finishes are available in all markets. Contact your local dealer for specific range details. KEF reserves the right, in line with continuing research and development, to amend or change specifications. E&OE.



OBSESSED WITH HIGH RESOLUTION

Ci specifications sheet

Motorised



| Model | | Ci3-80QT | Ci200.3QT |
|--|----|--|--|
| Series | | Q Series | Q Series |
| Nominal impedance | | 8Ω | 6Ω |
| Sensitivity (2.83V/1m) | | 87dB | 89dB |
| Frequency response (±6dB) with back can / rear enclosure | | 87Hz - 30kHz | 50Hz - 30kHz |
| Crossover frequency | | 300Hz, 3kHz | 1.8kHz |
| Drive units | LF | 2 x 75mm (3.0in.) Uni-Q | 200mm (8.0in.) Uni-Q |
| | MF | 75mm (3.0in.) | - |
| | HF | 15mm (0.6in.) | 25mm (1.0in.) |
| Recommended amplifier power | | 10 - 100 W | 10 - 100 W |
| Product external dimensions (H x W x D) | | 128 x 377 x 125 mm (5.04 x 14.84 x 4.92 in.) | 381 x 279 x 210 mm (15.0 x 10.98 x 8.27 in.) |
| Cut-out dimensions (H x W) | | 112 x 354 mm (4.41 x 13.94 in.) | 363 x 260 mm (14.29 x 10.24 in.) |
| Net weight | | 3.14kg (6.9 lbs) | 5.55kg (12.21 lbs) |
| Mounting depth from surface without back can | | 120mm (4.72in.) | 210mm (8.27in.) |

Outdoor



| Model | | Ventura 6 | Ventura 5 | Ventura 4 |
|---|------------------------|--|---|--|
| Series | | Ventura | Ventura | Ventura |
| Nominal impedance | | 6Ω | 6Ω | 6Ω |
| Sensitivity (2.83V/1m) | | 90dB | 89dB | 88dB |
| Frequency response (±6dB) | | 54Hz - 20kHz | 60Hz - 20kHz | 75Hz - 20kHz |
| Crossover frequency | | 3kHz | 3.8kHz | 3.5kHz |
| Drive units | LF | 160mm (6.5in.) | 130mm (5.25in.) | 115mm (4.5in.) |
| | HF | 25mm (1in.) | 25mm (1in.) | 19mm (0.75in.) |
| Recommended amplifier power | | 10 - 125 W | 10 - 100 W | 10 - 80 W |
| Product external dimensions (H x W x D) | Cabinet only | 300 x 226 x 219 mm (11.8 x 9 x 8.6 in.) | 262 x 197 x 189 mm (10.3 x 7.75 x 7.4 in.) | 231 x 172 x 173 mm (9 x 6.75 x 6.8 in.) |
| | With bracket and knobs | 300 x 226 x 263.5 mm (11.8 x 9 x 10.375 in.) | 262 x 197 x 235 mm (10.3 x 7.75 x 9.25 in.) | 235 x 172 x 203.2 mm (9.25 x 6.75 x 8 in.) |
| Net weight | | 3.8kg (8.4 lbs) | 2.85kg (6.28 lbs) | 2.4kg (5.3 lbs) |
| Operating temperature range | | -40°C to 70°C (-40°F to 158°F) | -40°C to 70°C (-40°F to 158°F) | -40°C to 70°C (-40°F to 158°F) |
| Certification | | IP65 | IP65 | IP65 |

Not all models / finishes are available in all markets. Contact your local dealer for specific range details. KEF reserves the right, in line with continuing research and development, to amend or change specifications. E&OE.